

Air, Water max 40°C 20 bar

BAYONET HOOKING



P/N

SIMPLE HOOKING



P/N

Supplied with:

- polyurethane hose with brass coupling
- brass swivel joint
- Viton® seals
- central shaft in galvanized steel
- inlet hose 1,5 m to connect the hose reel to the system



	P/N	P/N	Hose supplied	Connection	
				inlet	outlet
S. 260	260/11	-	11m 8x12 (911/11)	M 1/4"G	M 1/4"G
	260/12	-	11m 6x10 (901/11)	M 1/4"G	M 1/4"G
S. 260	-	261/11	11m 8x12 (911/11)	M 1/4"G	M 1/4"G
	-	261/12	11m 6x10 (901/11)	M 1/4"G	M 1/4"G

FIXED FOR SERVICE COLUMNS



P/N

SWIVELLING ENCLOSED PAINTED STEEL



P/N

Supplied with:

- polyurethane hose with brass coupling
- brass swivel joint
- Viton® seals
- central shaft in Delrin
- inlet hose 1,5 m to connect the hose reel to the system



	P/N	P/N	Hose supplied	Connection	
				inlet	outlet
S. 250	42438/11	-	12m 8x12 (911/12)	M 3/8"G	M 1/4"G
	42438/12	-	10m 10x14,5 (921/10)	M 3/8"G	M 3/8"G
	-	42608/11	12m 8x12 (911/12)	M 3/8"G	M 1/4"G
	-	42608/12	10m 10x14,5 (921/10)	M 3/8"G	M 3/8"G
S. 300	-	43108/12	12m 8x12 (911/12)	M 3/8"G	M 1/4"G
	-	43108/13	15m 8x12 (911/16)	M 3/8"G	M 1/4"G
	-	43108/14	20m 8x12 (911/21)	M 3/8"G	M 1/4"G
	-	43108/15	12m 10x14,5 (921/12)	M 3/8"G	M 3/8"G
	-	43108/16	15m 10x14,5 (921/16)	M 3/8"G	M 3/8"G



Atex 94/9 II 3 GD c IIB TX (only for Series 250-300)

Air, Detergent max 70°C 20 bar

FIXED ENCLOSED STAINLESS STEEL AISI 304



P/N

Supplied with:

- polyurethane hose with galvanized steel coupling
- stainless steel AISI 304 swivel joint
- Viton® seals
- central shaft in Delrin
- inlet hose 1,5 m to connect the hose reel to the system



	P/N	Hose supplied	Connection	
			inlet	outlet
S. 250	42708/11	12m 8x12 (811/12)	M 3/8"G	M 1/4"G
	42708/12	10m 10x14,5 (821/101)	M 3/8"G	M 3/8"G
S. 300	43208/12	12m 8x12 (811/12)	M 3/8"G	M 1/4"G
	43208/13	15m 8x12 (811/16)	M 3/8"G	M 1/4"G
	43208/14	20m 8x12 (811/21)	M 3/8"G	M 1/4"G
	43208/15	12m 10x14,5 (821/12)	M 3/8"G	M 3/8"G
	43208/16	15m 10x14,5 (821/16)	M 3/8"G	M 3/8"G



Atex 94/9 II 3 GD c IIB TX