

# Air, Water max 70°C 20 bar

For the SWIVELLING version add the suffix "/SO" at the P/N, For example: 268/10/SO

**FIXED PAINTED STEEL**



## Supplied with:

- polyurethane hose with galvanized steel coupling
- brass swivel joint
- Viton® seals
- central shaft in galvanized steel or PA6 Nylon
- inlet hose from 0,6 m to 1 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hose supplied	Connection	
			inlet	outlet
S. 270	268/10	without hose	M 3/8"G	F 3/8"G
	268/12	13m 10x14,5 (921/13)	M 3/8"G	M 3/8"G
	268/13	15m 8x12 (911/15)	M 3/8"G	M 1/4"G
	268/14	10m 6x10 (901/10)	M 3/8"G	M 1/4"G
	268/15	15m 6x10 (901/15)	M 3/8"G	M 1/4"G
S. 300	298/10	without hose	M 3/8"G	F 3/8"G
	298/12	15m 10x14,5 (921/15)	M 3/8"G	M 3/8"G
	298/13	18m 8x12 (911/18)	M 3/8"G	M 1/4"G
	298/14	8m 13x19 (961/8)	M 1/2"G	M 1/2"G
	298/15	12m 13x19 (961/12)	M 1/2"G	M 1/2"G
S. 350	348/10	without hose	M 3/8"G	F 3/8"G
	348/12	20m 10x14,5 (921/20)	M 3/8"G	M 3/8"G
	348/13	20m 8x12 (911/20)	M 3/8"G	M 1/4"G
	348/14	10m 13x19 (961/10)	M 1/2"G	M 1/2"G
	348/15	15m 13x19 (961/14)	M 1/2"G	M 1/2"G
S. 430	430/10	without hose	F 1/2"G	F 1/2"G
	428/11	10m 13x19 (961/11)	F 1/2"G	M 1/2"G
	428/12	15m 13x19 (961/15)	F 1/2"G	M 1/2"G



Atex 94/9 II 3 GD c X

## USES

