

# Connection hoses

## Inlet connection hoses connecting hose reel to the system or to equipment

P/N	Length	Pressure	ø mm Inside - Outside	Connection		
				Inlet	Outlet	Material
821/015	1,5 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	-	S. steel AISI 304
911/2	1,5 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	swivel hose holder ø10	brass
921/2	1,5 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	swivel hose holder F 3/8"G	brass
921/015	1,5 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	swivel hose holder ø10	brass
961/2	1,5 m	1/2" - polyurethane - 20 bar	13 x 19	M 1/2"G	swivel hose holder ø13,5	brass

## Polyurethane hoses

### Air, Water max 40°C 20 bar

P/N	Length	Characteristics - Pressure	ø Inside - Outside	Connection		
				Inlet	Outlet	Material
911/12	12 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	brass
911/16	15 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	brass
911/21	20 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	brass
921/10	10 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	connection 90°	brass
921/12	12 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	connection 90°	brass
921/16	15 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	connection 90°	brass

### Air, Water max 70°C 20 bar

P/N	Length	Characteristics - Pressure	ø Inside - Outside	Connection		
				Inlet	Outlet	Material
901/10	10 m	1/4" - polyurethane - 20 bar	6 x 10	M 3/8"G	M 1/4"G	brass
901/11	11 m	1/4" - polyurethane - 20 bar	6 x 10	M 1/4"G	M 1/4"G	brass
901/15	15 m	1/4" - polyurethane - 20 bar	6 x 10	M 3/8"G	M 1/4"G	brass
911/11	11 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	M 1/4"G	brass
911/15	15 m	5/16" - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
911/18	18 m	5/16" - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
911/20	20 m	5/16" - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
921/13	15 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
921/15	15 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
921/20	20 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
961/8	8 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass
961/10	10 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass
961/11	10 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass
961/12	12 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass
961/14	15 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass
961/15	15 m	1/2" - polyurethane - 20 bar	13 x 19	-	-	brass

### Air, Detergent max 70°C 20 bar

P/N	Length	Characteristics - Pressure	ø Inside - Outside	Connection		
				Inlet	Outlet	Material
811/12	12 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	AISI 304
811/16	15 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	AISI 304
811/21	20 m	5/16" - polyurethane - 20 bar	8 x 12	M 1/4"G	connection 90°	AISI 304
821/101	10 m	3/8" - polyurethane - 20 bar	10 x 14,5	M 3/8"G	connection 90°	AISI 304
821/12	12 m	3/8" - gomma nera - 20 bar	10 x 14,5	M 3/8"G	connection 90°	AISI 304
821/16	15 m	3/8" - gomma nera - 20 bar	10 x 14,5	M 3/8"G	connection 90°	AISI 304