

## **WASTE OIL SUCTION DRAINERS**





Floor waste oil drainer, 50 litres capacity, equipped with: ▶quick-release connector



OVERALL PHL P:630 H:235 L:780 mm



Floor waste oil drainer, 50 litres capacity, equipped with: ▶ suction tube

OVERALL PHL P:630 H:235 L:780 mm



Floor waste oil drainer, 95 litres capacity, equipped with: ▶quick-release connector

No.1 packing m<sup>3</sup> 0,200 8 kg 37,5

OVERALL P. H. DIMENSIONS P. H. P:725 H:200 L:1200 mm



Floor waste oil drainer, 95 litres capacity, equipped with: ▶pump P/N 0E33070

₩ No.1 packing m³ 0,200 kg 40

OVERALL P H DIMENSIONS P:725 H:200 L:1199 mm



Floor waste oil drainer, 150 litres capacity, equipped with: ►quick-release connector

OVERALL P. H L P:742 H:295 L:1238 mm



Floor waste oil drainer, 150 litres capacity, equipped with: ▶pump P/N 0E33/2011NHHV2

**™**No.1 packing m³ 0,330 **№** kg 61

OVERALL P H P:742 H:295 L:1238 mm

igtriangle The above items must not be used with flammable or corrosive fluids

P/N		0E42069	0E42070	0E42072	0E42073	0E42075	0E42076
Tank capacity	litres	50	50	95	95	150	150
Wheels		4 castors	4 castors	2 castors + 2 fixed	2 castors + 2 fixed	2 castors + 2 fixed	2 castors + 2 fixed
Emptying		by suction	by suction	by suction	pneumatic	by suction	pneumatic
Equipped with		quick-release connector	juction tube	quick-release connector	pump 0E33070	quick-release connector	pump 0E33/2011HHV2

## Pouring from the drainer to the tank.

The drained oil can be transferred from the collection bowl to the storage tank by suction with the incorporated probe or by an emptying pump connected to the fixed system or mounted directly on the collection basin



