


**PANTOGRAPH WASTE OIL SUCTION AND DRAINERS**
**P/N OE46064**

**Universal waste oil drainer with 65-litre tank**, equipped with:

- level gauge
- 14-litre collection bowl on cantilever arms
- removable tool tray
- not equipped with suction unit or probes

No.3 packing m<sup>3</sup> 0,247 kg 38,2

OVERALL DIMENSIONS P:570 H:1000 L:490 mm


**P/N OE46065**

**Air-operated universal oil suction-drainer with 65-litre tank**, equipped with:

- level gauge
- 14-litre collection bowl on cantilever arms
- removable tool tray
- P/N OE45560 set of probes (refer to page 22)

No.4 packing m<sup>3</sup> 0,310 kg 42,7

OVERALL DIMENSIONS P:570 H:1000 L:490 mm

P/N	OE46064	OE46065
Tank capacity	litres	65
Max draining capacity	litres	52
Bowl capacity	litres	14
Air pressure for depressurization	bar	-
Depressurization time	min	6,5 - 7
Noise level	dB	2
Suction speed at 70°-80°C	l/min	75
Total suction capacity	litres	1,5 - 2
Discharging hose	m	43 - 45
Suction hose	m	2
Max pressure for draining	bar	2
	0,5	0,5

**PANTOGRAPH WASTE OIL SUCTION AND DRAINERS**
**P/N OE46114**

**Universal waste oil drainer with 115-litre tank**, equipped with:

- level gauge
- 14-litre collection bowl on cantilever arms
- removable tool tray
- not equipped with suction unit or probes

No.3 packing m<sup>3</sup> 0,360 kg 51

OVERALL DIMENSIONS P:650 H:1500 L:580 mm


**P/N OE46115**

**Air-operated universal oil suction-drainer with 115-litre tank**, equipped with:

- level gauge
- 14-litre collection bowl on cantilever arms
- removable tool tray
- P/N OE45560 set of probes (refer to page 22)

No.4 packing m<sup>3</sup> 0,420 kg 54

OVERALL DIMENSIONS P:650 H:1500 L:580 mm

P/N	OE46114	OE46115
Tank capacity	litres	115
Max draining capacity	litres	97
Bowl capacity	litres	14
Air pressure for depressurization	bar	-
Depressurization time	min	6,5 - 7
Noise level	dB	3 - 3,5
Suction speed at 70°-80°C	l/min	75
Total suction capacity	litres	1,5 - 2
Discharging hose	m	85 - 90
Suction hose	m	2
Max pressure for draining	bar	2
	0,5	0,5

The above items must not be used with flammable or corrosive fluids