

PANTOGRAPH WASTE OIL SUCTION AND DRAINERS

P/N OE46116


Universal waste oil suction/drainer with transparent prechamber and with wheel-mounted 115-litre tank, equipped with: ▶ level gauge ▶ 14-litre collection bowl on cantilever arms ▶ removable tool tray ▶ P/N OE45560 set of probes (refer to page 22)

No.4 packing m³ 0,420 kg 58

OVERALL DIMENSIONS P:650 H:1500 L:580 mm



P/N		OE46116
Tank capacity	litres	115
Max draining capacity	litres	97
Bowl capacity	litres	14
Air pressure for depressurization	bar	6,5 - 7
Depressurization time	min	3 - 3,5
Noise level	dB	75
Suction speed at 70°-80°C	l/min	1,5 - 2
Total suction capacity	litres	85 - 90
Discharging hose	m	2
Suction hose	m	2
Max pressure for draining	bar	0,5



The tank mounted in all pantograph waste oil drainers is with antisplash filter

PANTOGRAPH WASTE OIL SUCTION AND DRAINERS

P/N OE46215


Universal waste oil suction/drainer with wheel-mounted 115-litre tank, equipped with: ▶ level gauge ▶ large 50-litre collection bowl on cantilever arms ▶ removable tool tray ▶ P/N OE45560 set of probes (refer to page 22)

No.4 packing m³ 0,520 kg 68

OVERALL DIMENSIONS P:700 H:1560 L:620 mm




P/N		OE46215
Tank capacity	litres	115
Max draining capacity	litres	97
Bowl capacity	litres	50
Air pressure for depressurization	bar	6,5 - 7
Depressurisation time	min	3 - 3,5
Noise level	dB	75
Suction speed at 70°-80°C	l/min	1,5 - 2
Total suction capacity	litres	85 - 90
Discharging hose	m	2
Suction hose	m	2
Max pressure for draining	bar	0,5




The collection tank can be placed on the floor or raised under an auto lift by means of the cantilever arms


⚠ The above items must not be used with flammable or corrosive fluids



Protection screen/filter splash guard and support base for filter



Tank with antisplash



To empty the tank with device already depressurised, open the bowl/tank connection valve and in a few seconds the oil will be sucked in the tank

