



MANUAL OIL DISPENSERS

P/N OE32016 *

Portable manual oil dispenser with 16-litre tank, equipped with:

▶ double-acting manual pump ▶ level gauge ▶ P/N OE24891 antislash funnel

No.1 packing m³ 0,080 kg 10,6 OVERALL DIMENSIONS P:255 H:860 L:225 mm

P/N OE32024 *

Manual oil dispenser with wheel-mounted 24-litre tank, equipped with:

▶ double-acting manual pump ▶ level gauge ▶ P/N OE24891 antislash funnel

No.1 packing m³ 0,090 kg 13,7 OVERALL DIMENSIONS P:280 H:890 L:330 mm

P/N OE32065 *

Manual oil dispenser with wheel-mounted 65-litre tank, equipped with:

▶ double-acting manual pump ▶ level gauge ▶ P/N OE24891 antislash funnel

No.1 packing m³ 0,185 kg 24 OVERALL DIMENSIONS P:600 H:880 L:420 mm

| P/N | | OE32016 | OE32024 | OE32065 |
|---|--------|----------|---------------|---------------|
| Tank capacity | litres | 16 | 24 | 65 |
| Structure | | portable | wheel mounted | wheel mounted |
| Delivery hose length | m | 2 | 2 | 2 |
| Quantity deliverable with complete cycle of lever | g | 220 | 220 | 220 |
| Max density oil deliverable | SAE | 240 | 240 | 240 |

AIR-OPERATED OIL DISPENSERS

P/N OE33016 *

Portable air-operated oil dispenser 16-litre tank, equipped with:

▶ level gauge ▶ P/N OE24891 antislash funnel ▶ delivery gun with flexible terminal

No.1 packing m³ 0,080 kg 9,9 OVERALL DIMENSIONS P:255 H:860 L:225 mm

P/N OE33024 *

Pneumatic oil dispenser with wheel-mounted 24-litre tank, equipped with:

▶ level gauge ▶ P/N OE24891 antislash funnel

▶ oil control valve with flexible terminal

No.1 packing m³ 0,090 kg 13,1 OVERALL DIMENSIONS P:280 H:890 L:330 mm

| P/N | | OE33016 | OE33024 |
|-----------------------------|--------|----------|---------------|
| Tank capacity | litres | 16 | 24 |
| Structure | | portable | wheel mounted |
| Delivery hose length | m | 2 | 2 |
| Gun hose length | m | 0,27 | 0,27 |
| Max density oil deliverable | SAE | 130 | 130 |



P/N OE24891

Antislash funnel. With antislash rim to prevent the liquid from spilling out when filling the tank

P/N OE32713 *

Digital litre-counter kit with partial and cumulative reading, complete with connection unions. Application between the pump and delivery hose allows the quantity of oil delivered to be controlled

* Do not use with flammable or corrosive liquids

* Not type-approved for public use