




## BRAKE-BLEEDING SECTION



## BRAKE-CLUTCH BLEEDING EQUIPMENT WITH 3 CHAMBERS

### P/N OE10705

Three-chamber brake-clutch bleeding device, complete with:

► P/N OE10801 two collection containers ► filler funnel

No.1 packing m<sup>3</sup> 0,065 kg 10,2

OVERALL DIMENSIONS P:450 H:650 L:250 mm

### P/N OE10805

Three-chamber brake-clutch bleeding device, complete with:

► P/N OE11001 set of plugs ► P/N OE10802 clutch bleeding tube ► P/N OE10801 two collection containers ► filler funnel

No.1 packing m<sup>3</sup> 0,065 kg 11,2

OVERALL DIMENSIONS P:450 H:650 L:250 mm

### P/N OE10807

Three-chamber brake-clutch bleeding device, complete with:

► P/N OE11004 set of plugs ► P/N OE10802 clutch bleeding tube ► P/N OE10801 two collection containers ► filler funnel

No.1 packing m<sup>3</sup> 0,065 kg 11,4

OVERALL DIMENSIONS P:450 H:650 L:250 mm

P/N		OE10705	OE10805	OE10807
Tank capacity	litres	5	5	5
Max working pressure	bar	2	2	2
Tank max pressure	bar	10	10	10
Delivery hose length	m	3	3	3
Safety valve	bar	10	10	10

The brake-bleeding device is equipped with an elastic inner membrane (2), which hermetically separates the oil contained in the oil tank (1), from the air contained in the air "expansion" tank (5) thus avoiding the risk of emulsion. It is also equipped with a third air reserve tank (high pressure air 8-10 bar) (6) which, delivered by means of a pressure regulator (3), enables several bleeding operations to be carried out at a constant pressure without having to recharge the device. The oil tank filler cap is equipped with a "reserve indicator" that signals when the fluid is finishing, and an air venting valve (4) to be used in the device activation phase.

## STANDARD SCREW CONNECTION PLUGS

### P/N OE11001

Series of standard screw connection plugs, supplied with P/N OE10805, complete with:

► 5 screw plugs: OE11000/A/D/F/I/T

► 1 universal plug OE11000/W

⚠ The above plugs can also be supplied individually. The universal plug OE11000/W can be used for many kind of cars and trucks

## SPECIAL SCREW CONNECTION PLUGS

### P/N OE11002

Series of special screw connection plugs, consisting of:

OE11000/B/C/E/G/H/K/L/M/P/R/U/X/Y/Z

⚠ The series of special plugs is only supplied by request

## UNIVERSAL PLUG W

### P/N OE11000/W

Universal plug W with 3 tapered plugs:

- 1) ø 20 mm
- 2) ø 28 mm
- 3) ø 45 mm

### APPLICATION EXAMPLES OF UNIVERSAL PLUG OE11000/W

