



* Not type-approved for public use

DIGITAL METER

P/N OE37780 *

Digital meters for oil and similar products max flow rate 35 l/min, equipped with:
 ▶ connection F 1/2" G ▶ Meter uses standard "off the shelf" two 1.5 v AAA batteries

No.1 packing m³ 0,0015 kg 0,85

OVERALL DIMENSIONS P:94 H:55 L:90 mm

P/N OE37781 *

Digital meters for oil and similar products max flow rate 70 l/min, equipped with:
 ▶ connection F 3/4" G ▶ Meter uses standard "off the shelf" two 1.5 v AAA batteries

No.1 packing m³ 0,0018 kg 1

OVERALL DIMENSIONS P:94 H:77 L:92 mm

P/N OE37782 *

Digital meters for oil and similar products max flow rate 100 l/min, equipped with:
 ▶ connection F 1" G + Flanges ▶ Meter uses standard "off the shelf" two 1.5 v AAA batteries

No.1 packing m³ 0,005 kg 1,35

OVERALL DIMENSIONS P:94 H:96 L:110 mm

P/N OE37785 *

Digital meters for antifreeze and windshield washing liquid max flow rate 40 l/min, equipped with:
 ▶ connection F 1/2" G ▶ Meter uses standard "off the shelf" two 1.5 v AAA batteries

No.1 packing m³ 0,0015 kg 0,85

OVERALL DIMENSIONS P:94 H:55 L:90 mm

P/N		OE37780	OE37781	OE37782	OE37785
Flow rate	l/min	35	70	100	40
Compatible fluids		oil and similar products, diesel fuel	oil and similar products, diesel fuel	oil and similar products, diesel fuel	antifreeze and windshield washing liquid
Body's material		aluminium	aluminium	aluminium	oxidized aluminium
Gear's material		POM	POM	POM	PVDF
Inlet		F 1/2"G	F 3/4"G	F 1"G + Flange	F 1/2"G
Outlet		F 1/2"G	F 3/4"G	F 1"G + Flange	F 1/2"G
Max working pressure	bar	70	70	70	70
Burst pressure	bar	200	200	200	200
Accuracy		± 0,3%	± 0,3%	± 0,3%	± 0,5%

