

TYRE INFLATOR HOSE REEL

P/N 0E52010


Inflation system comprising: ▶ P/N 260/11 hose reel
▶ inflation gun with pressure gauge ø 60 mm **type approved**
▶ P/N 260/01 bayonet hooking support




No.1 packing m³ 0,019 kg 6,8 OVERALL DIMENSIONS P: H L P:310 H:390 L:115 mm

ADVANTAGES

Quick and easy hooking on the bayonet bracket and quick connection to compressed air system



To prevent removal or theft of the hose reel it can be locked with a bolt or padlock



The locking pawl enables automatic stopping at the desired length (every 50 cm)

Constant strength spring contained inside the hose reel in hermetic case. Tested to resist up to 25000 cycles

Self-lubricating tube guide rollers

Outlet swivel joint 1/4" F

Adjustable hose-stop

Fluid conveyor joint with internal dimension to assure the best flow. In brass, acetalic resin and seals in Viton®

Robust ABS handle allows to move easily the hose reel

Drum support bushings in self-lubricating material

The pivoting bracket with bayonet hooking, easy to install, allows to remove the hose reel very easily

External cover made in ABS antishock, robust and resistant against strokes

P/N 260/01

Wall bracket with bayonet hooking. The placing of several brackets in the service points allows the hose reel to be easily moved to the various workstations

