

### CONNECTION HOSES

The hoses to be assembled on the hose reels must be suitable for the **working pressures specified on the label**



<b>P/N 932/1</b>	Hose M 1/4" x F 1/4"	▶ ø 1/4"	▶ 1m	▶ 20 bar
<b>P/N 932/2</b>	Hose M 1/4" x F 1/4"	▶ ø 1/4"	▶ 2m	▶ 20 bar
<b>P/N 935/4</b>	Hose M 1/4" x F 1/4"	▶ ø 1/4"	▶ 4m	▶ 400 bar
<b>P/N 935/13</b>	Hose M 1/4" x F 1/4"	▶ ø 1/4"	▶ 12m	▶ 400 bar
<b>P/N 935/18</b>	Hose F 1/4" x F 1/4"	▶ ø 1/4"	▶ 18m	▶ 400 bar
<b>P/N 957/1</b>	Hose M 3/8" x F 3/8"	▶ ø 3/8"	▶ 1m	▶ 400 bar
<b>P/N 957/2</b>	Hose M 3/8" x F 3/8"	▶ ø 3/8"	▶ 2m	▶ 400 bar
<b>P/N 957/06</b>	Hose M 3/8" x F 3/8"	▶ ø 3/8"	▶ 0,6m	▶ 400 bar
<b>P/N 957/10</b>	Hose M 1/4" x F 3/8"	▶ ø 3/8"	▶ 10m	▶ 400 bar
<b>P/N 963/25</b>	Hose M 1/2" x F 1/2"	▶ ø 1/2"	▶ 25m	▶ 150 bar

### NIPPLE



<b>P/N 0E66891</b>	Nipple M 1/4"G x M 1/4"G (tapered/cylindrical thread)
<b>P/N 0E66892</b>	Nipple M 1/4"G x M 3/8"G (cylindrical/cylindrical thread)
<b>P/N 0E66893</b>	Nipple M 1/4"G x M 1/2"G (cylindrical/cylindrical thread)

### NIPPLE



<b>P/N 0E66895</b>	Nipple M 3/8"G x F 1/4"NPT
<b>P/N 0E66896</b>	Nipple M 1/4"G x M 1/4"NPT
<b>P/N 0E66897</b>	Nipple F 1/4"G x M 1/4"NPT

### QUICK CONNECTOR



**P/N 0E60450**  
Female quick connector complete with check valve - F 1/4"BSP - max pressure 350 bar



**P/N 0E60451**  
Male quick connector complete with check valve - F 1/4"BSP - max pressure 350 bar