

POLAR TORQUE WRENCHES



7300 A DIGITAL TORQUE WRENCHES

ISO 6789, DIN 3122, EN 26789

- Digital torque wrench with reversible 36 teeth ratchet, for both clockwise and counterclockwise operation.
- Accuracy: $\pm 2\%$ (CW) / $\pm 3\%$ (CCW) from 20% to 100% of full scale
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 4 Torque units: Nm, kg-cm, in-lb and ft-lb.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 110 hrs.
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$.
- Storage temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM	■	L MM	G	
7314-1030	022055	1,5-30	0,01	1/4"	390	727	1
7338-1135	022062	6,8-135	0,1	3/8"	415	898	1
7312-1200	022078	10-200	0,1	1/2"	530	1333	1
7312-1340	022086	17-340	0,1	1/2"	650	1508	1

7300 B DIGITAL TORQUE WRENCHES WITH INTERCHANGEABLE HEADS

ISO 6789, DIN 3122, EN 26789

- Digital torque wrench with reversible 52 teeth ratchet, for both clockwise and counterclockwise operation.
- Accuracy: $\pm 2\%$ (CW) / $\pm 3\%$ (CCW) from 20% to 100% of full scale.
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 4 Torque units: Nm, kg-cm, in-lb and ft-lb.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 110 hrs.
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$.
- Storage temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.
- Large program in various inserts.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM	INSERT SIZE (W x H MM)	■	L MM	G	
7314-2030	022215	1,5-30	0,01	12 x 9	1/4"	388	768	1
7338-2135	022222	6,8-135	0,1	12 x 9	3/8"	408	936	1
7312-2200	022239	10-200	0,1	18 x 14	1/2"	518	1385	1
7312-2340	022246	17-340	0,1	18 x 14	1/2"	638	1555	1

