

## POLAR TORQUE WRENCHES



### 7400 DIGITAL TORQUE WRENCHES WITH ANGLE MEASUREMENT

ISO 6789, DIN 3122, EN 26789

- Digital torque wrench with reversible 36 teeth ratchet, for both clockwise and counterclockwise operation.
- Perform torque and angle thightnings in a single-step operation.
- Accuracy:  $\pm 2\%$  (CW) /  $\pm 3\%$  (CCW) from 20% to 100% of full scale and  $\pm 2\%$  for 90° rotation.
- Operation modes: Track (shows actual torque applied), Peak (shows maximum reached torque) and Angle.
- 5 measuring units: Nm, kg-cm, in-lb, ft-lb and angle.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 110 hrs.
- Operating temperature: -10°C ~ 60°C.
- Storage temperature: -20°C ~ 70°C.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM	■	L MM	G	☐
7414-0030	022017	1,5-30	0,01	1/4"	390	729	1
7438-0135	022024	6,8-135	0,1	3/8"	415	901	1
7412-0200	022031	10-200	0,1	1/2"	530	1338	1
7412-0340	022048	17-340	0,1	1/2"	650	1509	1

### 7614 1/4" DIGITAL MINI TORQUE WRENCH

ISO 6789, EN 26789

- Digital torque wrench with 60 teeth reversible ratchet bit holder, for both clockwise and counterclockwise operation.
- Drivers accept all standard 1/4" hex screwdriver bits.
- Accuracy:  $\pm 3\%$  (CW) /  $\pm 4\%$  (CCW) from 20% to 100% of full scale.
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 4 Torque units: Nm, kg-cm, in-lb and ft-lb.
- Acoustic and green/red LED signal at preset torque value.
- Battery life (continuous operation): 55 hrs.
- Operating temperature: -10°C ~ 60°C.
- Storage temperature: -20°C ~ 70°C.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM	INSERT SIZE (WXHMM)	L MM	G	☐
7614-0020	022123	1-20	0,01	1/4"	207	167	1

### 7638 3/8" DIGITAL MINI TORQUE WRENCH

ISO 6789, DIN 3122, EN 26789

- Digital torque wrench with reversible 60 teeth ratchet, for both clockwise and counterclockwise operation.
- Accuracy:  $\pm 3\%$  (CW) /  $\pm 4\%$  (CCW) from 20% to 100% of full scale.
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 4 Torque units: Nm, kg-cm, in-lb and ft-lb.
- Acoustic and green/red LED signal at preset torque value.
- Battery life (continuous operation): 55 hrs.
- Operating temperature: -10°C ~ 60°C.
- Storage temperature: -20°C ~ 70°C.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM	■	L MM	G	☐
7638-0085	022147	4,3-85	0,01	3/8"	239	387	1