



7514 A DIGITAL SCREWDRIVER

ISO 6789, EN 26789

- Digital torque screwdriver with quick-release bit holder, for both clockwise and counterclockwise operation.
- Drivers accept all standard 1/4" hex screwdriver bits.
- Accuracy: $\pm 3\%$ (CW) / $\pm 4\%$ (CCW) from 20% to 100% of full scale.
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 3 Torque units: cNm, kg-cm and in-lb.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 12 hrs.
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$.
- Storage temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY C NM	INCREMENTS NM		L MM		
7514-0050	022093	5,0-50	0,1	1/4"	193	142	1

7514 B/C DIGITAL SCREWDRIVERS

ISO 6789, EN 26789

- Digital torque screwdriver with quick-release bit holder, for both clockwise and counterclockwise operation.
- Drivers accept all standard 1/4" hex screwdriver bits.
- Accuracy: $\pm 2.5\%$ (CW) / $\pm 3.5\%$ (CCW) from 20% to 100% of full scale.
- Two operation modes: Track (shows actual torque applied) and Peak (shows maximum reached torque).
- 3 Torque units: cNm, kg-cm and in-lb.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 55 hrs.
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$.
- Storage temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.
- Comfortable, non-slip grip handle.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY C NM	INCREMENTS NM		L MM		
7514-0200	022109	10-200	0,1	1/4"	203	179	1
7514-0400	022116	20-400	0,1	1/4"	203	179	1

7700 DIGITAL TORQUE AND ANGLE ADAPTERS

ISO-6789

- Digital torque and angle adapter, for both clockwise and counterclockwise operation.
- Perform torque and angle tightenings in a single-step operation, using any tightening tool.
- The adapter can be used for verifying any mechanical torque wrench accuracy.
- Accuracy: $\pm 3\%$ from 20% to 100% of full scale and $\pm 2\%$ for 90° rotation.
- Operation modes: Track (shows actual torque applied), Peak (shows maximum reached torque) and Angle.
- 5 measuring units: Nm, kg-cm, in-lb, ft-lb and angle.
- Acoustic and green/red LED signal at preset torque value.
- Memory function with 9 preset torque values and 50 measurements.
- Battery life (continuous operation): 110 hrs.
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$.
- Storage temperature: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.
- Humidity: Up to 90% non-condensing.
- Supplied with test certificate and storage case.



ITEM NO.	5704196+	CAPACITY NM	INCREMENTS NM		SIZE MM		
7714-0030	022178	1,5-30	0,01	1/4"	86x85x60	163	1
7738-0135	022185	6,8-135	0,1	3/8"	85x85x75	216	1
7712-0200	022192	10-200	0,1	1/2"	85x85x80	240	1
7712-0340	022208	17-340	0,1	1/2"	85x85x80	240	1

