

**9605 CABLE TIES (100 PCS.)**

- UL Flame rating: 94V-2
- Material: Neutral 6/6 nylon
- Operating temperature: -40°C ~ 85°C.



ITEM NO.	5704196+	A x L MM	Ø MAX. MM	MIN. LOOP TENSILE STRENGTH KG	QTY PCS.	
9605-0005	017389	2,5 x 100	22	8,1	100	1
9605-0010	017402	2,5 x 150	36	8,1	100	1
9605-0015	017419	2,5 x 200	53	8,1	100	1
9605-0020	017426	3,6 x 140	33	18,2	100	1
9605-0025	017440	3,6 x 200	53	18,2	100	1
9605-0030	017457	3,6 x 300	76	18,2	100	1
9605-0035	017464	4,6 x 180	43	22,2	100	1
9605-0040	017488	4,8 x 200	50	22,2	100	1
9605-0045	017501	4,8 x 300	76	22,2	100	1
9605-0050	017525	4,8 x 370	102	22,2	100	1
9605-0053	026824	4,8 x 500	145	22,2	100	1
9605-0055	017532	7,6 x 250	67	54,4	100	1
9605-0060	017549	7,6 x 370	103	54,4	100	1
9605-0065	017556	7,6 x 540	159	54,4	100	1
9605-0070	017563	8,8 x 750	218	80,0	100	1
9605-0080	017587	12,4 x 650	195	114,0	100	1

**9606 UV CABLE TIES (100 PCS.)**


- UV weather resistant for outdoor application.
- UL Flame rating: 94V-2
- Material: Neutral 6/6 nylon
- Operating temperature: -40°C ~ 85°C.



ITEM NO.	5704196+	A x L MM	Ø MAX. MM	MIN. LOOP TENSILE STRENGTH KG	QTY PCS.	
9606-0005	017594	2,5 x 100	22	8,1	100	1
9606-0010	017617	2,5 x 150	36	8,1	100	1
9606-0015	017624	2,5 x 200	53	8,1	100	1
9606-0020	017631	3,6 x 140	33	18,2	100	1
9606-0025	017655	3,6 x 200	53	18,2	100	1
9606-0030	017662	3,6 x 300	76	18,2	100	100
9606-0032	043333	3,6 x 370	102	18,2	100	100
9606-0035	017679	4,6 x 180	43	22,2	100	100
9606-0040	017693	4,8 x 200	50	22,2	100	100
9606-0045	017716	4,8 x 300	76	22,2	100	100
9606-0050	017730	4,8 x 370	102	22,2	100	50
9606-0053	026831	4,8 x 500	145	22,2	100	50
9606-0055	017747	7,6 x 250	67	54,4	100	50
9606-0060	017754	7,6 x 370	102	54,4	100	25
9606-0065	017761	7,6 x 540	159	54,4	100	25
9606-0070	017778	8,8 x 750	218	80,0	100	10
9606-0080	017396	12,4 x 650	195	114,0	100	10
9606-0085	022000	12,4 x 1000	305	114,0	100	5

**9610 CABLE TIE MOUNTS (100 PCS.)**


- Adhesive modell for cable ties up to 4,8 mm width.
- The two largest sizes can be mounted by screws.
- UL Flame rating: 94V-2
- Material: Neutral 6/6 nylon
- Operating temperature: -40°C ~ 85°C.



ITEM NO.	5704196+	A MM	B MM	Ø HOLE MM	QTY PCS.	
9610-0010	017808	19,0 x 19,0	4,0	3,6	100	1
9610-0015	017815	28,0 x 28,0	5,3	5,5	100	1

**9611 UV CABLE TIE MOUNTS (100 PCS.)**


- Adhesive modell for cable ties up to 4,8 mm width.
- The two largest sizes can be mounted by screws.
- UV weather resistant for outdoor application.
- UL Flame rating: 94V-2
- Material: Neutral 6/6 nylon
- Operating temperature: -40°C ~ 85°C.



ITEM NO.	5704196+	A MM	B MM	Ø HOLE MM	QTY PCS.	
9611-0005	017822	12,7 x 12,7	3,2	-	100	1
9611-0010	017839	19,0 x 19,0	4,0	3,6	100	1
9611-0015	017846	28,0 x 28,0	5,3	5,5	100	1

**9620 STAINLESS CABLE TIES, TYPE 316 STEEL**

- Self locking ball bearing mechanism.
- Material: Stainless steel, type 316.



ITEM NO.	5704196+	A x L MM	Ø MAX. MM	MIN. LOOP TENSILE STRENGTH KG	QTY PCS.	
9620-0005	017853	4,6 x 200	62	90	100	1
9620-0010	017860	4,6 x 290	90	90	100	1
9620-0015	017877	4,6 x 360	113	90	100	1
9620-0020	017884	4,6 x 520	164	90	50	1
9620-0025	017891	4,6 x 680	215	90	50	1
9620-0030	017907	4,6 x 840	266	90	50	1